

HP-30B30PEL-M



3MPixel Smart LED Dual Light



Application
P6slite



3MPIXEL 
WIFI Camera Series



Feature

- * Pixels 3.0 Mega Pixel
- * Effective Pixels 2560*1440P
- * Compression H.264/H.265
- * TV System PAL / NTSC
- * Usable Illumination 0.001Lux
- * Ethernet RJ-45 (10/100M)
- * Protocol optional ONVIF2.4 / Hikvision
- * Smart Phone iPhone, iPad, Android, Android Pad
- * DWDR / WDR DWDR
- * Recording Mode NVR/NAS/CMS/Web
- * Audio G.711
- * Focus Length F1.3 3.6mm
- * Focus Control Fixed
- * Infrared LED 3PCS Smart dual-chip LED
- * Infrared Distance 35M
- * IR Status Under 10 Lux By CDS
- * Power Source DC12V±10%, 1000mA

Specification

Model	HP-30B30PEL-M
Pixels	3.0 Mega Pixel
Image Sensor	GC2083
Main processor	FH8852V201
Effective Pixels	2560*1440P
TV System	PAL / NTSC
Main stream	2560*1440/2303*1296/1920*1080/1280*720
Sub-stream	800*448/704*576/640*360/352*228
Electronic Shutter Time	Auto: PAL 1/1-1/10000Sec NTSC 1/1-1/10000Sec
Usable Illumination	0.001Lux
S/N Ratio	52dB
Video Output	Network
Network	
Ethernet	RJ-45 (10/100M)
Protocol	HTTP, TCP/IP, IPv4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, IP Search
Protocol optional	ONVIF2.4 / Hikvision
P2P	Support
POE	Support
WIFI	N/A
Video Delay	0.3S (Within the Lan)
Smart Phone	iPhone, iPad, Android, Android Pad
Frames Per Second	25Fps
Camera Features	
Day / Night	when people come in Monitor Area, it is warm light full color at night ,when people leave , will be infrared B/W at night
Compression	H.264 / H.265
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, BLC, FLK (Flicker Control)



Application
P6slite



3M PIXEL **HD**
WIFI Camera Series



Feature

- * Pixels 3.0 Mega Pixel
- * Effective Pixels 2560*1440P
- * Compression H.264/H.265
- * TV System PAL / NTSC
- * Usable Illumination 0.001Lux
- * Ethernet RJ-45 (10/100M)
- * Protocol optional ONVIF2.4 / Hikvision
- * Smart Phone iPhone, iPad, Android, Android Pad
- * DWDR / WDR DWDR
- * Recording Mode NVR/NAS/CMS/Web
- * Audio G.711
- * Focus Length F1.3 3.6mm
- * Focus Control Fixed
- * Infrared LED 3PCS Smart dual-chip LED
- * Infrared Distance 35M
- * IR Status Under 10 Lux By CDS
- * Power Source DC12V±10%, 1000mA

Specification

Model	HP-30B30PEL-M
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
DWDR / WDR	DWDR
Recording Mode	NVR / NAS / CMS / Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian
Audio	G.711
Lens	
Focus Length	F1.3 3.6mm
Focus Control	Fixed
Lens Type	Fixed
Night Vision	
Infrared LED	3PCS Smart dual-chip LED
Infrared Distance	35M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control
General	
Housing	Platic+Metal
Bracket	YES
IR Cut Filter	YES
Operation Temperature	-10 ~ +50 RH95% Max
Storage Temperature	-20 ~ +60 RH95% Max
Power Source	DC12V±10%, 1000mA
Dimension	187*60*72mm
Weight	0.4kg



Application
P6slite

