



5000 SERIES

IP CAMERA SUVEILANCE

HP-55B40PE



4M PIXEL HD
IP Camera Series





5000 SERIES

IP CAMERA SUVEILANCE

Specification



Feature

- * 1/2.8" CMOS sensor
- * Pixels 4.0MP / 3MP / 1080P / 720P
- * Iris Auto Electric Iris
- * Focal Length 3.6mm
- * IR SMD 18 Pcs (B/W)
- * IR Distance 20-30M.
- * IR Intensity Smart IR
- * Compression H.265 / H.265X
- * Dual steam
- * ONVIF
- * Audio In x1 (RCA)
- * Protection level IP66
- * Power 12V DC / PoE (IEEE802.3af)

Model	HP-55B40PE
Image Sensor	1/2.8" CMOS sensor
Pixels	4.0MP / 3MP / 1080P / 720P
Min. Illumination	Color: 0.01lux @ (F2.0, AGC ON) B/W: 0.001lux @ (F2.0, AGC ON)
Shutter Speed	1/50(1/60) ~ 1/10,000s
Day / Night	Auto (ICR) / Star Light Infrared (default) Full color / Black and white
Wide Dynamic Range	DWDR
White Balance	Auto
Gain Control	Auto
Backlight Compensation	BLC / Anti-flicker
Lens	
Mount Type	M12
Iris	Auto Electric Iris
Focal Length	3.6mm
Focus Mode	Manual focus
Infrared	
IR Type	IR SMD 18 Pcs (B/W)
IR Distance	20-30M.
IR Intensity	Smart IR
Video	
Compression	H.265 / H.265X
Image Resolution	Main stream: 4MP, 3MP, 2MP, 1MP Secondary stream: D1, HD1, QVGA
Main stream	4MP@20fps, 3MP@20fps, 2MP@25fps, 1MP@25fps
Sub-stream	D1@25fps, HD1@20fps, CIF@20fps, QVGA@20fps
Bitrate	0.1M-5Mpbs
Bitrate Control	CBR / VBR
Video Format	PAL / NTSC
Dual-stream	Dual stream
Caption	Date and time / Alarm / Customized
Motion Detection	Intrusion / Tripwire
Digital Noise Reduction	Auto
Digital Defog	Supported
Image Flip	Flip / Mirror
Audio	
Compression	G.711A
Network	
Network Protocols	TCP/IPv4, NTP, DHCP, DNS, RTSP, HTTP, DDNS, SMTP, UPnP, FTP, P2P
User Interface	IE, Chrome, Edge, Firefox, CU, Opera
Application Programming	ONVIF
Alarm	
Alarm Triggers	Intelligent alert / Video blind / Video loss / IP Conflict / Human detect
Alarm Events	Email notice / Mobile reported / FTP upload / Write log
Interfaces	
Ethernet	1 x 10/100M, RJ45 interface (Water-Proof Connector)
Audio In / Out	1 x RCA in
Environmental	
Operating Temperature	0C ~ +40C
Operating Humidity	90% RH (Non-Condensing)
Protection level	IP66
Electrical	
Power	12V DC / Ø5.5x2.1mm / PoE (IEEE802.3af)
Power Consumption	IR OFF : 2W / IR ON: 6W
Mechanical	
Case Material	Metal case
Weight	0.34Kg
Dimensions (mm)	183x71x60

4M PIXEL HD
IP Camera Series